

Airport Professional Park 2350 Post Road Warwick, Rhode Island 02886 Telephone: 401-736-3440 Fax: 401-736-3423 www.eaest.com

13 December 2006

Mr. Joseph T. Martella, II, Senior Engineer Rhode Island Department of Environmental Management Office of Waste Management Site Remediation Program 235 Promenade Street Providence, Rhode Island 02908


RE: RAWP Implementation Status Letter No. 2, Former Gorham Manufacturing Facility, Parcel B, 333 Adelaide Avenue, Providence, Rhode Island Case No. 2005-029
EA Project No. 61965.01

Dear Mr. Martella:

On behalf of the Providence Department of Public Property (City), EA Engineering, Science, and Technology, Inc. (EA) is providing this Remedial Action Work Plan (RAWP) Implementation Status Letter for the referenced site for your review and approval as necessary. Provision 6(e)(ii) of the Rhode Island Department of Environmental Management (the Department) Order of Approval (OA) dated 9 June 2006 for the referenced site states that the location of each interior methane/alarm (i.e., continuous within the building), as well as each proposed interior and subslab sample collection location be provided to the Department prior to installation. Please note that this letter is not intended to be a comprehensive description of the indoor methane monitoring/alarm system features, capabilities, or O&M procedures. The purpose of this letter is to: a) present the locations where methane will be continuously monitored within the building (i.e., the methane/alarm locations); b) to present the proposed interior air sampling locations; and c) to present the sub-slab vapor sampling locations to comply with the Order of Approval provision described above.

On-Site Meeting

On 16 November 2006, technical and sales representatives of DOD Technologies, Inc. (DOD, the supplier of the indoor methane monitoring/alarm system components), the Department, EA, and the electrical subcontractor responsible for installation of the system electrical components met at the former Gorham Manufacturing Facility for a demonstration of the components, an explanation of system operation, and to collectively discuss the optimal locations for the various system components. The selected locations for the system components presented herein are based upon the recommendations made by the DOD representatives, comply with the RAWP with respect to the number of monitoring locations and general areas of continuous monitoring, and are designed to provide the best possible level of access to designated responsible parties performing system operations and maintenance (O&M).





Overview of Main System Components and General System Operation

The Department-approved indoor methane monitoring/alarm system consists of eight continuous methane monitors, a central controller, and an auto dialer to notify designated, responsible parties (e.g., school officials, environmental engineering contractor, etc.) of alarm conditions should they be detected. A diagram illustrating the conceptual functionality between the sensors and the controller is provided in Attachment A. Per the recommendation of the DOD representatives, the sensor housings can be physically located up to approximately 125 feet away from the actual indoor air monitoring locations. Individual polypropylene tubing runs will connect the individual sensor units to the various school building areas from which the continuous monitoring will occur. Each tubing run will be connected to the corresponding air sampling intake on the individual sensor units, which will communicate data with the central controller and auto dialer.

Location of Main System Components and Monitoring Locations

The central controller will be installed in the school administration work room area. Placement of the controller in close proximity to school administrators will facilitate prompt responses to audible/visual alarms and will prohibit unauthorized access or possible vandalism to the controller. Four of the eight system monitors will be installed in the main electrical room located within the east wing of the school building (just north of the main corridor running east-west in central portion of the school), and the remaining four monitors will be installed in the electric room within the west wing of the school building (adjacent to the mechanical room). The electrical rooms will only be accessible by authorized personnel.

Tubing emanating from the four sensors in the east wing electrical room will be run to the following locations where indoor air will be continuously monitored by the sensors:

- student classroom located within the east wing of the school building just south of the guidance office/waiting area;
- student classroom located directly across corridor from boys and girls restrooms within east wing of the school building;
- · cafeteria; and
- kitchen storage room away from natural gas food service equipment.

Tubing emanating from the four sensors in the west wing electrical room will be run to the following locations where indoor air will be continuously monitored by the sensors:

- meeting room located within west wing of the school building just north of the computer lab:
- student classroom located across corridor from science lab within west wing of the school building;



- north-west corridor located in close proximity to elevator (per Department suggestion to facilitate monitoring potential methane intrusion via the elevator shaft area); and
- gymnasium.

These continuous monitoring locations are illustrated on the Figure in Attachment B along with the sensor and central controller locations. All tubing will by run over drop ceilings or, in areas where no drop ceilings and the potential for tampering exists, within protective PVC piping. The tubing will terminate inside the various rooms/areas described above just under the finished ceiling height, with the exception of the cafeteria and gymnasium. Since there are no traditional ceilings in these areas, the tubing will terminate in the gymnasium and cafeteria at a height of approximately 12 feet above the finished floor. This height will facilitate access by authorized personnel for O&M (if needed) but will also minimize the potential for tampering by unauthorized personnel (e.g., sporting event spectators).

Proposed Sub-Slab and Indoor Air Sampling Locations

In accordance with the RAWP and the OA, three representative sub-slab vapor samples and three representative indoor air samples are required prior to sub-slab venting system start-up, after system start-up but prior to building occupancy, and quarterly thereafter. The proposed sampling locations are discussed below.

EA proposes to collect the sub-slab vapor samples from monitoring points MP-2, MP-5, and MP-8, which generally correspond to areas beneath the northern, western, and eastern portions of the school building, respectively, and provide representative coverage of the sub-slab region. Please refer to the Figure provided in Attachment C for the location of these three monitoring points.

With respect to indoor air sampling, EA proposes to collect the representative indoor air samples within rooms or areas on the first floor of the school building that roughly correspond to (i.e., located above) the sub-slab sampling locations (MP-2, MP-5, and MP-8) and three of the continuous indoor methane monitoring locations. These locations are within the cafeteria, the west wing student classroom, and the east wing student classroom opposite the boys and girls rooms. Collecting the representative indoor air samples in these corresponding locations will facilitate comparative analysis of the data and evaluation of potential vapor migration into the school building (or absence thereof) from the subsurface.



We trust that this correspondence satisfies the OA Provision 6(e)(ii). However, if you have any questions or require additional information, please do not hesitate to contact me at 401-736-3440, Ext. 216.

Sincerely,

EA ENGINEERING, SCIENCE, AND TECHNOLOGY, INC.

Peter M. Grivers, P.E., LSP Project Manager

PMG

Attachments

cc: A. Sepe, Providence Department of Public Property

B. Wagner, Esq., RIDEM Legal Services

K. Owens, RIDEM Office of Waste Management

L. Hellested, RIDEM Office of Waste Management

T. Gray, RIDEM/AW&C

C. Walusiak, RIDEM Office of Waste Management

S. Rapport, City of Providence Law Department

J. Boehnert, Partridge, Snow, & Hahn

T. Deller, Providence Redevelopment Agency

J. Simmons, City of Providence

J. Hartley, GZA

S. Fischbach, RI Legal Services

J. Pichardo, Senator - District 2

G. Simpson, Textron

T. Slater, Representative

Former Gorham Site, Parcel B – Knight Memorial Library Repository

Attachment A Methane Monitoring System Components



Auto Dialer

500ppm alarm level is pager or phone when Auto Dialer will dial a

> shown). Provided with 8 alarm & strobe light (not

programmable relays.

connect to up to 8 PS-7

PDC Controller can

units. PDC provides

concentration at each

point, programmable alarm levels, audible

4-20 signal provides reached


concentration data to

central controller

PS-7 CH4 0-1000ppm gas detection units installed through out school

Appendix B

Figure Illustrating Monitoring System Component Locations



Appendix C

Figure Illustrating Proposed Sub-Slab Sampling Locations

SUB-SLAB VENTING SYSTEM LOCATION S. ENGINE FRING. 2350 Post Rood Verwick, Rt 02585 (401) 736-3440 EL MANE B196503_C-1_C-2_UMC RANKS NUMERR APRIL 2006 PAGE SHARES PAGE

PAGE HAVE BY

PAGE HAVE BY NS SHOWN PROVIDENCE, RHODE ISLAND PROPOSED PROVIDENCE HIGH SCHOOL - PRACEL "B" FORMER CORHAM MANUFACTURING PROPERTY 8 SALING CONCRETE SAMES.
POR CONTROL SAMES.
PORCE OF TOOLED MICH. SCHOOL SAME SONS.
SEARCH WITH PREVIOUS THE PORCE OF TOOLED MICH. SCHOOL MICH.
SEARCH WITH PREVIOUS THREE THANK CHEEK PATER. D MARNING CROST: SUB-SLAW VENTURE, SYST SAVE OF WISHILLING SOOD TO PROPERTY. THE SYSTEM SEED TO PROPERTY. THE SYSTEM STATE OF WILL BE STATE OF STATE OF STATE OF STATE OF STATE STATE OF STATE O 1. If IS RECOMMENSED THAT BIS DESCRIPTOR OF THE RESET CAUGHTO HARM SECTION 2.2.5 OF PERFORMED 19.37 FOR HALD PESON AND OFFICIALLY STORE THE CAUGHT SECTION AND OFFICIAL STOREM THAT CAUGHTS NOT WHITNING IN TO RULDING CODES IN SOME ARREAS REQUEST.

TO PRICE A WORLD MASS, EXCOR ROCKERS,

FOR THE STAND STANDS TO REPORT AND REPOR C. WSTALL A. A. DAWETER WAY PRE FROW THE SLAD TO THE SOOT B PADDE ISLAND STATE BUILDING CODE, LATEST EDITON D. PAUCH PRETUTION IN THE DESIGN AND CONSTRUCTION OF SONDS AND DIRER LANG ELLONGS. THEIR PRINTING WITH ACCEPTION AREA 1995, U.S. ENVIRONMENTAL PROTECTION ACCION. A 24 YEST POE SAUL BE 4" DAMERS.
B BALDOG COOKS BREDING COOKS IN YOUR CASES OF COOKS BREDING COOKS OF WILLIAMS.
SOE DAMERS SECTIONS OF BREDINGS.
SOE DAMERS SECTION STREAM, INSTANTIANS AND ALCOHOLOGY. B. INSTALL A KTAT ARCA BT ST DEEP RAIDON SUCTON PET LINGER THE STAB IN THE ACCRECATE A PLACE A CONTINUOUS 6" LAYER OF CLEAN COMPSE ACCHECATE BENEATH THE SLAB C. DCDENARM SATTY AND HEALTH AS CAR ADMINSTRATOR (USHA) REGILATION 25 CAR PARK 1978 - OCCURNIBALL SAFETY AND HEALTH A THE PRECEDENCE CONTROLLE TON SUB-SIAM WHING STREAMS IS CONTROLLE ACCREDITED ASTRONOMY SPECIFICATION TO CONTROLL ACCRECATION TO CONTROLL ACCRECATION TO CONTROLLE ACCRECATION. E INDUSTIBAL VENTLATON 1914 EDITOR. J BANNILL DE RECOMENDED PORCTICES, COMMETTE DV INDUSTRAL VENTLATION, LA M. 1965 5. 889 ASHRAE FUNDAMENTALS JAHIOBOOM DIAMPITR 14, 240E 34.4, RICHRE 17 S 784 S 785 S 86 $(\pm)(\pm)$ РКОРОЅКО МОК РКОВС (ТРР.) — -∏≟ ¤ 5 × II (ii) £33 (i) (E) ·(å) Į × 20 SUCTION PRIMIC UNDER BUILDING STAB (FYP.) 100H 0 STACK THROUGH SUCTION PIT NUMBER (TYP.) FROPDSED SUB-SLAB **(9**) (P) (c)(a) (3) ව මණ්ඩම ව මකිව