



Spill Containment Basin Replacement Information, Instructions, and Application Form

When does a spill containment basin need to be replaced?

A spill containment basin (SCB), commonly referred to as a "spill bucket", must be replaced when it is physically damaged, no longer capable of holding liquid, or if it fails a tightness test. A SCB may also be required to be replaced as part of the DEM Office of Air Resources Stage I requirements. This information and application applies to SCBs on both the fill and Stage I Vapor line, and the same requirements apply to all spill containment basins.

Can I repair a spill containment basin?

No - spill containment basins cannot be repaired, they can only be replaced.

What spill containment basins can be installed?

All new and replacement spill containment basins must be:

- Double Walled
- Capable of periodic interstitial monitoring
- Able to contain a minimum of 3 gallons of liquid
- Stage I EVR CARB-approved
- Threaded on; ("Slip On" or "Slip Over" spill buckets are no longer allowed)

Do I need prior approval from DEM to replace a spill containment basin?

Yes, you need prior approval from the Office of Air Resource to replace an SCB, prior notification the UST program is not typically needed for the replacement of spill containment basins or modifications or replacement of the risers associated with SCB replacement. Call our office at (401) 537-4539 for more information and contact OAR for Stage I requirements at: DEM.OARStageI@dem.ri.gov . Please be aware that some cities or towns may require additional municipal permits and/or approval from the local fire department prior to installation or replacement.

Who can replace a spill containment basin?

All modifications and repairs, including SCB replacement, must be performed by a qualified installer in good standing with DEM who has a valid Gas Station Ltd license issued by the RI Dept of Labor and Training.

Does an Environmental Consultant need to be present during the installation?

Maybe. DEM strongly suggests all SCB replacements and associated risers have an environmental consultant present in order to identify and address releases and contamination early. Early intervention typically results in easier and less expensive remediation. However, an environmental consultant is only required to be present and screen soils anytime there is evidence of a release to the surrounding peastone or soil, if the SCB failed a tightness test, or damage to the SCB or riser is observed, including, but not limited to, cracks, holes, excessive corrosion, pitting, delamination, or damaged, missing, or heavily degraded gaskets/or seals.

What do I do if contamination is discovered?

If evidence of contamination or a release of product is discovered during the replacement of the spill containment basin, you should immediately call the DEM UST Management Program at (401) 537-4353 to report your findings. Evidence of a release may include, but is not limited to, stained soil or peastone, strong petroleum odor, visible sheen, or visible product. DO NOT CALL EMERGENCY RESPONSE FOR SOIL EXCEEDANCES!

What testing is required for a Spill Containment Basin replacement?

After installation, a full-level hydrostatic test must be performed on each SCB that was replaced, and a primary wall tightness on each UST must be performed. All tests must be performed by a DEM-licensed 3rd party tester.

What paperwork is required?

The installer must submit the following documents to the UST Program within 14 days:

- Completed Spill Containment Basin Replacement Application Form
- Results of a completed spill containment basin hydrostatic tightness test showing a passing result
- UST primary wall tightness test results performed by a 3rd party DEM-licensed tester
- If applicable, a summary report written by the Environmental consultant summarizing their findings;

Where do I submit the paperwork?

RI DEM - LRSMM: UST Program
ATTN: Kevin Gillen
235 Promenade Street
Providence, RI 02908

Spill Containment Basin (Spill Bucket) Replacement Form

This form must be submitted to DEM within 14 days of spill containment basin replacement

Facility	Facility Name: <input style="width: 350px;" type="text"/>	DEM Facility ID# <input style="width: 120px;" type="text"/>
	Physical Address: <input style="width: 320px;" type="text"/>	City/Town: <input style="width: 240px;" type="text"/>

UST System Owner	UST Owner Name: <input style="width: 680px;" type="text"/>		
	Primary Contact Name: <input style="width: 680px;" type="text"/>		
	Mailing Address: <input style="width: 280px;" type="text"/>	City: <input style="width: 150px;" type="text"/>	State: <input style="width: 80px;" type="text"/>
	Phone #: <input style="width: 150px;" type="text"/>	E-mail: <input style="width: 400px;" type="text"/>	

Installer	Firm/Contractor Name: <input style="width: 680px;" type="text"/>		
	Primary Contact Name: <input style="width: 680px;" type="text"/>		
	Mailing Address: <input style="width: 280px;" type="text"/>	City: <input style="width: 150px;" type="text"/>	State: <input style="width: 80px;" type="text"/>
	Phone #: <input style="width: 150px;" type="text"/>	E-mail: <input style="width: 400px;" type="text"/>	

Environmental Consultant	Firm/Contractor Name: <input style="width: 680px;" type="text"/>		
	Primary Contact Name: <input style="width: 680px;" type="text"/>		
	Mailing Address: <input style="width: 280px;" type="text"/>	City: <input style="width: 150px;" type="text"/>	State: <input style="width: 80px;" type="text"/>
	Phone #: <input style="width: 150px;" type="text"/>	E-mail: <input style="width: 400px;" type="text"/>	

of Spill Containment Basins Replaced: Replacement Reason: Replacement Date:

DEM UST #	UST Contents	Which SCBs were replaced?		Manufacturer	Model #
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>
<input style="width: 50px;" type="text"/>	<input style="width: 150px;" type="text"/>	Fill Pipe	Stage I Port	<input style="width: 100px;" type="text"/>	<input style="width: 100px;" type="text"/>

Check here if UST vapor lines are manifolded and share a common Stage I port

Was it necessary to saw-cut the surrounding concrete to install the new SCB? Yes No

If yes, give the approximate size of the excavation (feet): Width: Length: Depth:



If you suspect a release of petroleum or other hazardous materials has occurred, call DEM at (401) 537-4353 immediately



Were any UST risers removed in order to replace the SCB? Yes No

Were any UST risers modified, cut, re-threaded, or extended? Yes No

If yes, explain the modification and identify which risers were impacted:

[Empty text box for modification details]

Were new UST risers installed? Yes No

If yes, identify which risers were replaced:

[Empty text box for replaced risers]

If yes, what material are the new risers constructed of? Stainless Steel Galvanized Steel Dielectric Wrapped Steel



UST primary wall Tank Tightness and hydrostatic testing of the UDC must be performed within 24 hours of completion of the SCB replacement. Any failed result is required to be reported immediately by completing the notification form on our website or by calling (401) 222-2797. All test results, this form, and environmental consultant summary report must be submitted within 14 days

Draw a rough sketch of the UST system and show which SCBs were replaced and, if applicable, which risers were modified or replaced:

[Large empty box for drawing the UST system]

I certify under penalty of law that I prepared this document and the information contained is accurate and truthful. I have contacted the local fire department, utilities and have obtained any necessary local permits or permissions, and fulfilled any necessary requirements related to the replacement of components. I have reported any evidence of contamination, including, but not limited to, soil staining, odor, sheen, or visible product to DEM. I have read and understand the testing requirements related to spill containment basins and underground storage tanks, and I am aware that there are significant penalties for submitting false information

Installer Name (Printed): [Text box]

RI DLT License #: [Text box]

Installer Signature: [Text box]

Date: [Text box]