# No Discharge Compliance Program Inspection Protocol

## **Purpose of inspection is threefold:**

- 1. To identify the type of MSD aboard each vessel;
- 2. To confirm that the MSD is properly sealed/secured/configured to prevent the overboard discharge of sewage when in RI waters; and
- 3. To ensure that the owner/operator is aware of the no-discharge law, available pump-out opportunities, and appropriate sewage disposal options.

### 1. Type of MSDs

- ◆ Type I treats sewage by chemical means, e.g., maceration and chlorination (no holding tank).
- ♦ Type II treats sewage by biological means, e.g., bacteria (no holding tank).
- ♦ Type III device that stores sewage in a holding tank; or a device that incinerates the waste.

Any vessel with a marine toilet but without a Type I, Type II, or Type III MSD is not in compliance with state or federal law and cannot be issued a decal.

#### 2. Status of MSD

- A. Vessels with a holding tank (Type III MSD) and <u>no through-hull fitting</u> allowing sewage to be discharged overboard are in compliance with RI's no-discharge law.
  - ♦ Upon inspection and certification of compliance, these vessels are to be issued a **green** decal.
- B. Vessels with a holding tank (Type III MSD) and with a through-hull fitting that allows sewage to be discharged overboard, must have the MSD properly secured in a manner that prevents overboard discharges (when operating in RI waters).

Properly secured means:

• Closing the valve that leads to the through-hull fitting and removing the

handle:

- Closing and padlocking the valve that leads to the through-hull fitting; or
- Using a non-releasable wire-tie to hold the valve that leads to the throughhull fitting in the closed position.
- ◆ Upon inspection and certification of compliance, these vessels to be issued a **yellow** decal.
- C. Vessels with a Type I or Type II MSD (no holding tank) must have the MSD properly secured in a manner that prevents overboard discharges (when operating in RI waters).

Properly secured means:

- Closing the seacock and removing the handle;
- Padlocking the seacock in the closed position;
- Using a non-releasable wire-tie to hold the seacock in the closed position;
  or
- ♦ Locking the door to the space enclosing the toilet with a padlock or door handle key lock.
- ♦ Upon inspection and certification of compliance, these vessels are to be issued a **yellow** decal.

#### 3. Public Education & Awareness

♦ All boat owners/operators shall be provided with DEM flyer titled *Managing Boat Waste in Rhode Island's No Discharge Area*, which includes information on how to comply with RI's No Discharge Law, and how to access map of pumpout facility locations.

**Issuance of Decals** 

- Decals must be displayed in a **prominent position** on each vessel that passes inspection.
- It is recommended that the decals be affixed to the port side, or on the transom.
- ♦ Inspectors should provide the decals to the vessel owner/operator, advising them as to proper placement. Inspectors may affix the decals themselves, but only if specifically asked to do so by vessel owner/operator, in the location requested by the owner/operator.
- ♦ It is in the vessel owner/operator's best interest to ensure that the decal is prominently displayed.

#### **Collection of Fees**

♦ For each inspection, inspectors may charge up to \$35/vessel, plus up to \$25 for each additional toilet aboard the vessel.