Facility Name	Contact	Phone	Email
	pply to your facility so that proper air pollution e itions see page 2. For further clarifications about S Coating Operations (250-RICR-120-05-19).		
Surface Coating Operation	Application Process	Coatir	ng Type
Coil Coating	Electrostatic spray		General (1 component)
Fabric Coating	HVLP spray		General (multi-component)
Vinyl Coating	Flow coat		Extreme high gloss
Flatwood Paneling Coating	Roller		Extreme performance
Large Appliance Coating	Dip (includes electrodeposition)		Heat resistant
Magnet Wire Coating	Airless spray		Solar absorbent
Metal Furniture Coating	Rotary screen (fabric coating)		Metallic
Wood Furniture Coating	Flat screen (fabric coating)		Stain
Miscellaneous Metal Parts Coating	Stencil		Fog coat
Miscellaneous Plastic Parts Coating	Air dried		Texture coat
Paper Coating	Baked		Adhesive
Film Coating	Exterior parts		Clear coat
Foil Coating	Interior parts		Electric-insulating varnish
Steel Drum Coating	Vacuum-metalizing		Architectural
Automotive/transportation Coating	Aerosol		Military
Business Machinery Coating	Powder		Sealer
Pleasure Craft Coating	Pretreatment		Filler
Wood Products Manufacturing	Other (specify):		Primer
(See regulation Part 35 or 250-RICR-120-05-35	5 for applicability)		Topcoat
Other (specify):			Flexible
			Basecoat
If applicable to your facility, check the boxes	below. If not, leave blank.		Other (specify):
Mixing Room: personnel mix formulat	ions to specifications		
Mixing Room: personnel only stir form	nulations already in drums		
Bulk Storage Tanks for VOCs other tha	n fuel (specify how many:)		
Air Pollution Control Equipment: RIDE	M approval No No. of days op	erated (witho	out malfunctions)
Return to:		•	Air Pollution Inventory Form D, Page 1
DEM.AirInventory@dem.ri.gov			

DEM.AirInventory@dem.ri.gov Air Pollution Inventory, Office of Air Resources 235 Promenade Street, Providence, RI 02908-5767

Definitions

Aerosol: a spraying coating method using a pressurized container with a gas propellant.

Air-dried: a method of drying the coating by the use of air or forced warm air at temperatures up to ninety degrees Celsius (90°C) or one hundred and ninety-four degrees Fahrenheit (194°F).

Airless spray: a coating spray application system using high fluid pressure, without compressed air, to atomize the coating.

Baked: a method of drying the coating by curing at a temperature at or above ninety degrees Celsius (90°C) or one hundred ninety-four degrees Fahrenheit (194°F).

Business machine: a device that uses electronic or mechanical methods to process information, perform calculations, and print or copy information or convert sound into electrical impulses for transmission.

Dip application: a method of applying a coating by surface submersion into and removal from a coating bath.

Electrostatic spray: a method of applying a coating by electrically charging the coating particles or coating droplets.

Flow coating: a non-atomized technique of applying coating to a substrate using a fluid nozzle in a fan pattern with no air supplied to the nozzle.

HVLP spray: a method of applying a coating using a high-volume, low-pressure spray application system that is designed to operate at air pressures between 0.1 and 10 pounds per square inch gauge.

Large appliance coating: the application of a coating to the surface of component metal parts (including, but not limited to, doors, cases, lids, panels and interior parts) of any residential or commercial washer, dryer, freezer, range, refrigerator, water heater, dishwasher, trash compactor, air conditioner, or other similar products.

Pleasure craft: any marine or freshwater vessel manufactured or operated primarily for recreational purposes.

Powder coating: a type of electrostatic coating process using a dry powder without a solvent and cured into a uniform coat.

Pretreatment: a process where a coating or wash primer is applied directly to fiberglass or metal surfaces to provide surface etching, adhesion, corrosion resistance, and ease when stripping.

Roller application: a coating method using a machine that continuously transfers coating on to the substrate through a set of oppositely rotating rollers.

Stencil coating: a coating that is applied over a stencil to a substrate at a thickness of one mil or less of coating solids. Stencil coats are most frequently letters, numbers, or decorative designs.

Vacuum metalizing: the process of evaporating metals inside a vacuum chamber and depositing them on a substrate to achieve a uniform metalized layer.

For Additional Definitions refer to Part 19: Control of Volatile Organic Compounds from Surface Coating Operations (250-RICR-120-05-19).

Return to:

Air Pollution Inventory Form D, Page 2

Rhode Island Department of Environmental Management

2023 Air Pollution Inventory



Air Dried

Baked

Check one:

Application Process (see first page for reference)

Surface Coating Basic Spreadsheet

Substrate

Coating Formulation Name	(see pg 1 for reference)	Used	Total VOC in Coating (wt %)	Total VOC in Coating (lb/gal)	Density or Specific Gravity (lb/gal)	Solvent Component Name or CAS no. in coating (see coating's SDS)				
						(wt %)	(wt %)	(wt %)	(wt %)	(wt %)

Information supplied on this form should be for calendar year 2023. You may find it helpful to contact your supplier/vendor to obtain all the required information. Most will supply you with a list of all purchases along with a copy of each product's SDS. The information received from your supplier/vendor may be submitted in lieu of filling out the Table only if the name of product, the amount used, and the application process are clearly identified with the attached SDS. The total VOC in the coating by weight percentage or the lbs of VOC per gallon can be found in the SDS or product data sheet. Report only coatings that you have purchased more than one gallon of in 2023. If the coating is thinned prior to application, please contact the Office of Air Resources for further directions. See page 4 for further Instructions on how to fill in the Table above.

Return to:

Facility Name

DEM.AirInventory@dem.ri.gov Air Pollution Inventory, Office of Air Resources Promenade Street, Providence, RI 02908-5767

Instructions for the Table

Coating Formulation Name

Fill in this box with the product name of a coating that your facility used. This is generally located in Section 1 (Identification) of the Safety Data Sheet for the coating.

Coating Type

Fill in this box with the coating type. This is what your facility used the coating for, and this information can also be found in Section 1 (Identification) of the Safety Data Sheet.

Amount Used

Fill in this box with the amount of this coating your facility used. This can be determined from adding the amount your facility stored in the beginning of January to the amount your facility purchased from your suppliers during the year, then subtracting the remaining amount your facility stored at the end of December. If your facility does not carry inventory at the beginning or end of the year, then submit only the purchased amount.

Total VOC in Coating (wt %) and/or Total VOC in Coating (lb/gal)

Fill in one or both boxes. The total Volatile Organic Compound content in the coating is recorded as a weight percentage (wt %) and/or density (lb/gal) and can be found in Section 9 (Physical and Chemical Properties) of the Safety Data Sheet.

Density or Specific Gravity

Fill in this box with the density or specific gravity of the coating. The density is recorded as lb/gal or g/mL while the specific gravity is without units and usually between 0.7 and 1.5. This information is located in Section 9 (Physical and Chemical Properties) of the Safety Data Sheet.

Solvent Component Name or CAS no. in Coating (see coating's SDS)

The information for this section of the Table can be found in Section 3 (Composition/Ingredients) of the Safety Data Sheet. Each known component of the formulation is recorded with common name and/or a CAS number and its weight percentage (wt %) in the formulation. For each formulation component that is a VOC, write either the component's name or CAS number in the space above the (wt %) and then record the weight percentage of the component in the coating underneath. Only record the weight percentages of that component for each coating in that column. Use a different column for each component. If you need to add columns for more VOC components in the coating, fill out another Table with an indication that this is a continuation of the coatings in the first Table.

Return to:

Rhode Island Department of Environmental Management 2023 Air Pollution Inventory

Supplemental Chemical Use Survey



			Page of
Facility Name			· ·
Signature of Person Completing I	Form		Date
Note: Report only those subs Coating/Printing/Formul		lity which have <u>not</u> been	reported on the Surface
VOC or Regulated			
Substance Name & CAS Number	CAS:	CAS:	CAS:
Type of Operation			
Starting Inventory* (1/1/2023)			
Amount Purchased in 2023			
Ending Inventory* (12/31/2023)			
Amount Manifested and % of that manifested			
waste which was the Regulated Substance*	%	%	%
Amount of Substance Released to Air			
Air Pollution Control Equipment and	Type:	Туре:	Type:
Approval No.	Appr. No.:	Appr. No.:	Appr. No.:
Capture Efficiency (Percent)			
Overall Efficiency (Percent)			

Return to: DEM.AirInventory@dem.ri.gov

*If known

Air Pollution Inventory, Office of Air Resources

Air Pollution Inventory Form D, Page 5

(attach additional sheets if necessary)

235 Promenade Street, Providence, RI 02908-5767

Instructions for Supplemental Chemical Use Survey

Regulated Substance - List all Volatile Organic Compounds (VOC) and all chemicals listed on the list entitled "Listed Toxic Air Contaminants" that were used at and/or emitted from the facility. Provide a CAS number, usually available on your MSDS. Please note that all miscellaneous volatile organic compounds (VOCs) used in excess of 100 pounds must be reported even if the name is not specifically listed on the Listed Toxic Air Contaminants List.

Type of Operation - Describe the process in which the listed substance was used (for example, degreasing, plating, wipe cleaning, etc.).

Starting Inventory - Report the amount of the substance present on site at the start of the year, if known. State whether the amount is given in <u>pounds</u> or gallons. Please provide data in <u>pounds</u> if possible.

Amount Purchased - Report the amount of the substance purchased in the year and indicate whether the number given is in <u>pounds</u> or gallons. Again, provide data in <u>pounds</u> if possible.

Ending Inventory - Report the amount of the substance present on site at the end of the year, if known. State whether the amount is given in <u>pounds</u> or gallons.

Amount Manifested - Report the amount (in <u>pounds</u>) of the regulated substance which was manifested as hazardous waste and the percentage of that waste that was this chemical.

Amount of Substance Released to Air - Calculate the amount of the substance emitted to air. Include both fugitive and stack emissions. **Attach documentation of the calculations used.** You may find it necessary to make other mass balance adjustments such as an amount disposed in a landfill or discharged to a POTW. Label carefully.

Describe Air Pollution Control Equipment - Provide a short description of the equipment used to control emissions of the regulated substance, if any. Examples follow:

Type: Carbon adsorber, venturi scrubber, VOC incinerator, baghouse, etc.

Include RI DEM Approval Number, if known.

Capture: Give the capture efficiency for this chemical.

Overall: Give the overall control efficiency of the control equipment for this chemical.

Overall Efficiency = Capture Efficiency x Destruction or Recovery Efficiency

Note: On a separate sheet, please provide any additional information pertinent to your processes or air pollution control equipment that will assist us in calculating an accurate emissions estimate from your facility for this reporting year.